



18K



25K, 30K, 36K, 40K, 48K, 60K



18K, 25K



30K, 36K



40K, 48K



60K

Black Panel
Controller: YR-E17A (มีสาย)



PB-950KB (B)



YL-HQS01
Standard



YR-E17A
Optional

รับประกันคอมพรสเซอร์ 10 ปี
รับประกันตัวเครื่อง 5 ปี
ฟรีค่าบริการหลังการขายทุกรายการ 5 ปีแรก

MODEL	Set	HCSI-18PSR32	HCSI-25PSR32	HCSI-30PSR32	HCSI-36PSR32	HCSI-36BTR32	HCSI-40BSR32	HCSI-40BTR32	HCSI-48BSR32	HCSI-48BTR32	HCSI-60BTR32	
	ID	HCSI-18PSR32F	HCSI-25PSR32F	HCSI-30PSR32F	HCSI-36PSR32F	HCSI-36BTR32F	HCSI-40BSR32F	HCSI-40BTR32F	HCSI-48BSR32F	HCSI-48BTR32F	HCSI-60BTR32F	
	OD	1U-18S1R32CP	1U-25S1R32CP	1U-30S1R32CP	1U-36S1R32CP	1U-36T3R32C	1U-40S1R32C	1U-40T3R32C	1U-48S1R32C	1U-48T3R32C	1U-60T3R32C	
Power supply	Ph/v/Hz	220/1/50	220/1/50	220/1/50	220/1/50	380/3/50	220/1/50	380/3/50	220/1/50	380/3/50	380/3/50	
Rated cooling	Capacity	Btu/h	18,813(6,800-20,100)	26,082(9,500-27,300)	30,806(11,900-34,000)	528(13,600-38,900)	39,000(13,600-40,100)	40,800(15,300-42,000)	40,800(15,300-42,000)	48,410(17,700-49,000)	49,545(17,700-50,000)	60,960(15,300-61,000)
	Power Consumption	W	1480	2320	2640	3330	3600	4350	4350	6306	5384	5030
	Running current	A	6.80	10.65	12.12	17.58	17.58	19.88	7.22	28.8	8.8	8.49
	SEER	BTU/hr/W	16.24	17.13	17.78	17.58	17.58	16.49	16.49	14.26	14.84	15.42
	Energy Class		5	5	5★	5★	5★	5	5	5	5	5
Start current	A	3	3	4	4	4	5	3	5	3	3	
Remote Controller (S)		YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	YL-HQS01	
Wired Controller (O)		YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	
Indoor	Indoor air flow (H/M/L)	m3/h (CFM Max)	760/700/620/500	1260/1070/820/680	1470/1260/1050/940	1680/1530/1320/1190	1680/1530/1320/1190	1950/1600/1440/1200	1950/1600/1440/1200	1950/1600/1440/1200	2050/1600/1440/1220	
	Indoor noise level (H/M/L)	dB(A)	40/37/35/32	36/33/29/26	41/36/33/29	41/36/33/29	41/36/33/29	45/42/38/34	47/44/38/34	47/44/38/34	49/46/41/37	49/46/41/37
Panel	Panel Model		PB-620KB	PB-950KB	PB-950KB	PB-950KB	PB-950KB	PB-950KB	PB-950KB	PB-950KB	PB-950KB	
	External dimensions(W/D/H)	mm	620x620x60	950x950x50	950x950x50	950x950x50	950x950x50	950x950x50	950x950x50	950x950x50	950x950x50	
	Shipping dimensions(W/D/H)	mm	660x660x115	1000x1000x110	1000x1000x110	1000x1000x110	1000x1000x110	1000x1000x110	1000x1000x110	1000x1000x110	1000x1000x110	
	Panel Net/Shipping Weight	KG	2.8/4.5	6.5/9	6.5/9	6.5/9	6.5/9	6.5/9	6.5/9	6.5/9	6.5/9	
Indoor dimension	Unit (L/W/H)	(mm)	570/570/260	840*840*204	840*840*246	840*840*246	840*840*246	840*840*288	840*840*288	840*840*288	840*840*288	
	Packing (L/W/H)	(mm)	718/680/380	990*990*310	990*990*310	990*990*310	990*990*310	990*990*380	990*990*380	990*990*380	990*990*380	
	Net/Gross weight	(Kg)	19/22	27/32	31/36	31/36	31/36	32/38	32/38	32/38	32/38	
Outdoor	Outdoor air flow	m3/h	2500	2500	3500	3800	3800	5000	5000	5500	5500	7400
	Outdoor air flow	CFM	1475	1475	2064	2240	2240	2950	2950	3250	3250	4363
	Outdoor noise level	dB(A)	54	54	57	59	59	56	58	58	59	59
	Tube Material		Inner Grooved copper	Inner Grooved copper	Inner Grooved copper	Inner Grooved copper	Inner Grooved copper	Inner Grooved copper	Inner Grooved copper	Inner Grooved copper	Inner Grooved copper	Inner Grooved copper
	Compressor	Type	Mitsubishi Electric	Mitsubishi Electric	Mitsubishi Electric	Mitsubishi Electric	Mitsubishi Electric	Mitsubishi Electric	Mitsubishi Electric	Mitsubishi Electric	Mitsubishi Electric	Mitsubishi Electric
Outdoor dimension	Compressor	Brand	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	
	Unit (L/W/H)	mm	820*338*614	820*338*614	920*372*760	920*372*760	920*372*760	950*370*965	950*370*965	950*370*965	950*370*1350	
	Packing(L/W/H)	mm	977/400/735	977/400/735	1085*487*843	1085*487*843	1085*487*843	1050/450/1095	1050/450/1095	1050/450/1095	1050/485/1500	
	Net/Gross weight	kg	38/42	38/42	52/57	57/62	60/65	76/86	76/86	76/86	76/86	101/116
	Type		R32	R32	R32	R32	R32	R32	R32	R32	R32	R32
Refrigerant	Charge	g	970	1130	1280	1500	1650	1900	1900	1900	3500	
	Additional weight	g/m	20	45	45	45	45	45	45	45	45	
	Liquid side	mm	6.35	9.52	9.52	9.52	9.52	9.52	9.52	9.52	9.52	
Refrigerant pipe	Gas side	mm	12.7	15.88	15.88	15.88	15.88	15.88	15.88	15.88	19.05	
	Max. length	m	20	20	25	30	30	50	50	50	70	
	Max. height	m	10	10	10	20	20	30	30	30	30	
	Min. length	m	5	5	5	5	5	5	5	5	5	
Operation temperature range	°C	16~30	16~30	16~30	16~30	16~30	16~30	16~30	16~30	16~30	16~30	
Ambient temperature range	°C	18~43	18~43	18~43	18~43	18~43	18~43	18~43	18~43	18~43	18~43	

